

# Single SIP Account Entry-Level Business **WIFI** IP Phone Model Number: M7



NICEUC M series IP Phone is a multi-access network, easy deployment, excellent sound quality IP Phone. It supports 1 SIP account, which features elegant appearance and easy to operate. It is an entry-level IP Phone specially designed for business office, suitable for enterprise unified communications.

#### About NICEUC Communication Co., Ltd

NICEUC Communication Co., Ltd. is a professional developer and manufacturer of VoIP products. NICEUC provides VoIP communication devices solutions for small and medium sized businesses, as well as large mission-critical enterprise environments.

Over the 16 years since its establishment, NICEUC Communication has built a strong engineering team and solid partnerships with IP communication chipset providers, such as HUAWEI, ZTE.

### Why choose M series

- Modern and elegant design, exquisite workmanship, popular surface shape
- Top structure design and materials, excellent software and hardware adjusting ensure the quality of audio input and output, especially the use of strong power and full frequency horn, super-size sound chamber, makes the hands-free like big speaker, brings wonderful sound experience for personal office, which enables employees holding small hands-free meeting freely
- WiFi is convenient for user's deployment, seamlessly and easily be used in the wireless office network
- Dual-core CPU, processing of voice and application independently, improve voice quality and application processing speed
- Rich application, perfectly compatible with leading IP PBX platform
- Communication security, signal encryption, media encryption, HTTPS for WEB management and uploading & downloading configuration files
- Convenient deployment and maintenance, support remote deployment by Internet
- Power adaptor protection avoid machine damage caused by error operation
- 3 meters long, durable, non-crimping handset line
- Strong package guarantee the long-distance transportation

### Basis functions

- 132\*52 graphic character dot matrix with backlight LCD, 1 SIP account
- Call Forward, Call Transfer, Call Waiting, Hotline, Call Hold, Auto Answer, Caller ID, Redial, Mute
- DND, Local 3-Way Conferencing, Speed Dial, Voice Mail, Local Phonebook (up to 1000 entries)
- Direct IP call without SIP proxy, Black list, White list, Dialed/Received/Missed call (each 200)
- Call Center Headsets mode

### IP PBX Features

Intercom, Paging, Call pickup, Call park, Anonymous call, Anonymous call rejection, Hold on music, Conference Call, Group pickup, DND & Call forward state synchronization, Call Recording

### Multiple-language

English, German, Italian, French, Spanish, Portuguese, Russian, Chinese, Arabic, Polish, Turkish, Hebrew

### Advanced Features

LDAP, Microsoft active directory (AD) server, XML remote phonebook

### Audio Features

- 8 own ring tone, 2 custom ring tone article, 8 volume adjustable + Mute mode, Narrowband codec: G.711(a/μ), G.729A/B/AB, G.726, iLBC,
- Wideband codec: G.722, L16, Support VAD, CNG, AEC, PLC, AJB, AGC, Full-duplex speakerphone with AEC

### Network Features

- LAN / PC: support bridge mode, Open VPN support, SIP connection mode: Proxy mode, and P2P mode, Support DNS SRV (RFC3263).

Tel: +62-821-14611732

PT. Tata Telemedia Nusantara | [www.tatatelemedia.co.id](http://www.tatatelemedia.co.id)

Address: Jl. Pejaten Raya 12A Pejaten Barat, Jakarta 12510

• NAT transverse: STUN mode. DTMF: In-band, RFC2833, SIP INFO, Support QoS, HTTP / HTTPS web server, Package tracing export, Syslog

### WiFi Features

IEEE 802.11b/g/n, Enhanced support for IEEE 802.11e QoS, Support APA, APA2, IEEE802.11i (WPA, WPA2) authentication

### Security

VLAN, LLDP, IEEE802.1X, TLS, HTTPS, SRTP (RFC3711), Digest authentication using MD5/MD5-sess, AES encryption for configuration files, Phone lock, User and administrator level access control

### Management

Configurable through web interface/phone, Provisioning: Auto-provision via FTP/TFTP/HTTP/HTTPS, DHCP Option 66, Remote Provision Service (RPS)

### Physical

Power Interface: DC 5V-1A, PoE power supply: IEEE 802.3af Class 2, 2x RJ45 10/100M or 100/1000M adaptive Ethernet ports, 1x RJ9 headphone jack, 1x RJ9 handset jack

### Keys Features

1 status indicator, 3 soft keys, 5 navigation keys, 1 volume keys, 8 function keys (menu, cancel, hold, voicemail, mute, headphone, redial, hands-free)

### Temperature and Humidity

Operating temperature: -10 ~ 50°C, Operating humidity: 10 ~ 90%

### Package

Qty/CTN: 10 PCS, G.W/CTN: 11KG, Gift box size: 280mm (L)\*210mm(W)\*78mm(H), Carton Meas: 425mm(L) \*415mm(W) \*300mm(H)

### PBX Compatibility

Broadsoft, Asterisk, Elastix, Trixbox, Freeswitch, Huawei, Avaya, Mitel, Unify, ZTE, Epygi

### Certifications

CE: EN60950, FCC: Part15

