

# GlobalTime Clock Display

---

## NTP Digital Clock GTD 366

NTP digital clock ini dilengkapi dengan Text display diproduksi oleh GlobalTime Precision, Co., Ltd, yang populer digunakan untuk mentransfer time atau waktu melalui jaringan kabel LAN / Rj45 connector. Saat ini sumber NTP clock tersedia secara gratis di Internet. Perangkat ini melakukan sinkronisasi waktu secara otomatis tanpa intervensi manual. Perangkat Jam Digital ini mendapatkan waktu yang sangat akurat dari internet atau intranet berbasis NTP Server.

NTP Digital Clock berupa tampilan LED 2.3 inch dilengkapi dengan running text display terlihat akurat pada jarak pandang 15 meter.

2.3" Digital PoE Clock with Date/ Text Display- GTD366



**TYPE**  
GTD 366

### KEY FEATURES

- Can display date or text (Maximum static text display: 13 characters, If text is over 13 characters, choose to roll, or alternate)
- Time is automatically set by Simple Network Time Protocol(SNTP) - no master clock or serial connection required.
- Uses PoE ( Power over Ethernet) for easy installation and operation
- Static IP or DHCP addressing
- Display time in 12 or 24 hours format
- Supports any time zone.
- Supports countdown function
- Automatic daylight saving time

- Environmentally friendly: the light intensity of the digits is adjustable by the software
- Provides NTP server configuration.
- If connection to NTP server is lost the clocks will continue to run on the built-in time base. When the connection is restored it will synchronize automatically.
- Can be single sided ( has one display screen) or double sided ( has two display screens)
- Mounting options: pendant, cantilever, surface
- Alarm Function is optional
- Temperature and Humidity display is optional

### APPLICATION

- NTP clock display, Time display, Synchronized clock
- Text display
- Very reliable and easy-to-use network time appliance for modern networks and business operations

### PROTOCOL SUPPORT

- RFC 1119/1305 NTP v2/v3/v4
- RFC 1769/2030 SNTP v2/v3/v4
- DHCP

### MECHANICAL/ENVIRONMENT

- Case: Metal in Black or White
- Size: 43cm x 15.5cm x 6.3cm, Weight: 2kg
- Display: 2.3 inch digit (56mm character), 8\*8 dot matrix (38mm high)
- Viewing Distance: 50 feet - 15 meters
- Mounting Options: pendant, cantilever, surface Power Consumption: less than 10W
- Operating temperature: -10°C~65°C
- Storage temperature: -40°C~85°C
- Operational humidity: 0~90%, non-condensing, IEC 60068-2-78Cb, IEC 60068-2-30Db

### CERTIFICATION

- FCC/CE/RoHS

### CONTACT

PT. Tata Telemedia Nusantara, direct sales

WhatsApp +62 818 8020-45 | Direct call +62 821 146 117-32

WhatsApp  
0818 8020-45

PT. Tata Telemedia Nusantara

Address: Jl. Pejaten Raya 12A Pejaten Barat, Pasar Minggu - Jakarta Selatan 12510  
www.tatatelemedia.co.id | +62 821 146 11732 | sales@tatatelemedia.co.id